

Types & Specifications	Front panel shape	Rated working voltage (V)		Electric Principle	Illustration and outline size	Mounting hole size
		Direct Current(DC)	Alternating Current (AC)			
AD11-22/21-W1A Position Signal Lamp	Round flat	24、48、110 IF: 15mA 220 IF:10mA				Opening diameter 22.3mm or 25.5mm (Adding conversion ring)
AD11-22/41-W1A Position Signal Lamp			220、380 IF:15mA			
AD11-22/22-W2A Position Signal Lamp	Square	24、48、110 IF: 15mA 220 IF:10mA				
AD11-22/42-W2A Position Signal Lamp			220、380 IF:15mA			
AD11-22/22-W3A Position Signal Lamp	Square	24、48、110 IF: 15mA 220 IF:10mA				
AD11-22/42-W3A Position Signal Lamp			220、380 IF:15mA			
AD11-22/21-W4A Position Signal Lamp	Round flat	24、48、110 IF: 15mA 220 IF:10mA				
AD11-22/41-W4A Position Signal Lamp			220、380 IF:15mA			
AD11-22/22-W5A Position Signal Lamp	Square	24、48、110 IF: 15mA 220 IF:10mA				
AD11-22/42-W5A Position Signal Lamp			220、380 IF:15mA			
AD11-22/21-W6A Position Signal Lamp	Round flat	24、48、110 IF: 15mA 220 IF:10mA				
AD11-22/41-W6A Position Signal Lamp			220、380 IF:15mA			

Note: Wiring mode is of anti-electric shock structure and it is recommended to use preferentially.